















AMF TOPIQ® SONIC ELEMENT



- AMF TOPIQ® Sonic element is a frameless and jointless ceiling raft, featuring the AMF TOPIQ® Strong Edge Technology. It also benefits from a fully colour coated face and reverse laminate fleece
- The monolithic ceiling raft design offers excellent sound absorption properties and when installed gives the appearance of a free floating ceiling cloud



AMF TOPIQ® SONIC ELEMENT

Thickness (mm)		40																																										
Dimensions (mm) Additional sizes and shapes on request		<table border="0"> <tr> <td>Trapezoid</td> <td>1170 x 870</td> <td>Rectangle</td> <td>1200 x 600</td> </tr> <tr> <td>Hexagon</td> <td>1170 x 1013</td> <td>Rectangle</td> <td>1780 x 1180</td> </tr> <tr> <td>Left Parallelogram</td> <td>1170 x 1170</td> <td>Rectangle</td> <td>1800 x 900</td> </tr> <tr> <td>Right Parallelogram</td> <td>1170 x 1170</td> <td>Rectangle</td> <td>2380 x 1180</td> </tr> <tr> <td>Square</td> <td>1180 x 1180</td> <td>Circle</td> <td>Ø800</td> </tr> <tr> <td></td> <td></td> <td>Circle</td> <td>Ø1200</td> </tr> </table>	Trapezoid	1170 x 870	Rectangle	1200 x 600	Hexagon	1170 x 1013	Rectangle	1780 x 1180	Left Parallelogram	1170 x 1170	Rectangle	1800 x 900	Right Parallelogram	1170 x 1170	Rectangle	2380 x 1180	Square	1180 x 1180	Circle	Ø800			Circle	Ø1200																		
Trapezoid	1170 x 870	Rectangle	1200 x 600																																									
Hexagon	1170 x 1013	Rectangle	1780 x 1180																																									
Left Parallelogram	1170 x 1170	Rectangle	1800 x 900																																									
Right Parallelogram	1170 x 1170	Rectangle	2380 x 1180																																									
Square	1180 x 1180	Circle	Ø800																																									
		Circle	Ø1200																																									
System		Wire hanger																																										
Weight		6.0 kg/m ²																																										
Colour & design		White Colour																																										
Sound absorption		<p>EN ISO 354</p> <table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>Equivalent Absorption Area Aobj*</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>1180 x 1180 suspension height 190mm</td> <td>0.40</td> <td>1.20</td> <td>2.20</td> <td>2.40</td> <td>2.40</td> <td>2.30</td> </tr> <tr> <td>1780 x 1180 suspension height 190mm</td> <td>0.80</td> <td>2.10</td> <td>3.10</td> <td>3.30</td> <td>3.50</td> <td>3.40</td> </tr> <tr> <td>2380 x 1180 suspension height 190mm</td> <td>0.80</td> <td>2.70</td> <td>4.20</td> <td>4.40</td> <td>4.50</td> <td>4.30</td> </tr> <tr> <td>Ø1200 suspension height 150mm</td> <td>0.40</td> <td>1.00</td> <td>1.70</td> <td>1.80</td> <td>2.00</td> <td>1.90</td> </tr> </tbody> </table> <p>*Values shown are the average of the 3 one third octave band values</p>	Frequency f (Hz)	125	250	500	1000	2000	4000	Equivalent Absorption Area Aobj*							1180 x 1180 suspension height 190mm	0.40	1.20	2.20	2.40	2.40	2.30	1780 x 1180 suspension height 190mm	0.80	2.10	3.10	3.30	3.50	3.40	2380 x 1180 suspension height 190mm	0.80	2.70	4.20	4.40	4.50	4.30	Ø1200 suspension height 150mm	0.40	1.00	1.70	1.80	2.00	1.90
Frequency f (Hz)	125	250	500	1000	2000	4000																																						
Equivalent Absorption Area Aobj*																																												
1180 x 1180 suspension height 190mm	0.40	1.20	2.20	2.40	2.40	2.30																																						
1780 x 1180 suspension height 190mm	0.80	2.10	3.10	3.30	3.50	3.40																																						
2380 x 1180 suspension height 190mm	0.80	2.70	4.20	4.40	4.50	4.30																																						
Ø1200 suspension height 150mm	0.40	1.00	1.70	1.80	2.00	1.90																																						
Fire reaction		Euroclass A2-s1,d0 as per EN 13501-1																																										
Light reflectance		Up to 88%																																										
Humidity resistance		95%																																										
Cleanability	 																																											
Sustainability																																												

Flexible design and adjustable to various heights using steel cables.

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.